

Apply tape and RTV at splits labeled "A"


## Flat Head Screw Mounting

PROSLR for shaft diameters up to 15.748" [400mm]

- 1: PROSLR-\_\_\_\_\_-1FHA4 Supplied with 4, 8-32 x 1.25 inch FHCS  
2, Aluminum tape 2" x 1"  
1, Tube RTV Silicone
- 2: PROSLR-\_\_\_\_\_-2FHA4 Supplied with 4, M4 x .7 x 30mm FHCS  
2, Aluminum tape 2" x 1"  
1, Tube RTV Silicone
- 3: Contains 6 Rows of Conductive Micro Fibers
- 4: To be installed in Conjunction With AEGIS® Colloidal Silver Coating PN CS015

Fiber  $\phi$  = Shaft  $\phi$  - .060"  $\pm$ .010 [Shaft  $\phi$  - 1.52mm  $\pm$  .25]

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN: inch [mm]	 <b>ELECTRO STATIC TECHNOLOGY</b> AN ITW COMPANY
UNTOLERANCED DIMENSIONS $\pm$ .010 [0.254mm]	
DATE: 4/25/2016	31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256 PHONE (207)998-5140 FAX (207)998-5143
ENGINEER: M. Roman	PROSLR Split Bearing Protection Ring w/ Dust Barrier
	PART NUMBER: PROSLR Split template -_FHA4 REV A