

$\varnothing 2.600 \pm .010$   
 [66.04  $\pm$  0.25]

SGR OD =  $\varnothing 2.100 \pm .010$   
 [53.340  $\pm$  0.254]

$\varnothing 1.185$   
 [30.10]

$\varnothing 1.021$   
 [25.93]

.295 MAX  
 [7.49]

.370 Max Over  
 Mounting Clamps

**Notes:**


Supplied with:  
 3, Standard Mounting Clamps and  
 3, M3 x 0.5 x 8mm SHCS With Appropriate Lock Washers

**Conductive Micro-Fiber To Suit**  
**1.061 [26.95] to 1.105 [28.07] Shaft Diameters**

Patented Technology US Patent 8,199,453; 8,169,766; 7,193,836

THEREIN, ARE THE EXCLUSIVE PROPERTY OF ELECTRO STATIC TECHNOLOGY ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT CONSENT, BE REPRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT BUSINESS WITH E.S.T.

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN:  
inch [mm]



ELECTRO STATIC TECHNOLOGY  
 AN ITW COMPANY

UNTOLERANCED DIMENSIONS  
 $\pm .010$  [0.254mm]

31 WINTERBROOK ROAD, MECHANIC FALLS, MAINE 04256  
 PHONE (207)998-5140 FAX (207)998-5143

AEGIS® SGR w/ clips

DATE: 1/15/2013

PART NUMBER: SGR-25.9-2

REV A

ENGINEER: A. Gen